



BHS1.com

***Battery Carts & Carriages
Roller Transfer Cart,
Hardwood Transfer Cart,
Traveling Battery Transporter***



BHS Battery Carts offer versatile, dependable alternatives for battery transport demands. Battery Carts are built with operator safety and convenience in mind and can be custom built to unique specifications.

Battery Carts & Carriages

Roller Transfer Cart

The BHS Roller Transfer Cart (RTC) is available in three models with widths from 18" to 40" (457 mm to 1016 mm). For added safety and convenience, roller transfer carts are rated at 3,000 lb (1360 kg) capacity and come standard with floor locks. Note: Roller height required when ordering.

Features & Benefits

- Floor locks for added convenience
- 6" (152 mm) phenolic casters for low rolling resistance
- Spark-proof rollers provide extra levels of safety
- Heavy duty construction means long, dependable life
- All models meet OSHA standards
- Custom designs available to meet your specifications
- 5" to 13" (127 mm to 330 mm) roller heights available
Note: Units with roller heights below 10" (254 mm) use outboard mounted casters and roller heights 10" (254 mm) up to 11" (279 mm) use 5" (127 mm) casters
- Rated 3,000 lb (1360 kg) capacity for heavy loads

Available Models

RTC-18

RTC-30

RTC-40

Product Specifications

| | RTC-18 | RTC-30 | RTC-40 |
|--------------------------|----------------|-----------------|-----------------|
| Compartment Width | 18" / 457 mm | 30" / 762 mm | 40" / 1016 mm |
| Compartment Depth | 40" / 1016 mm | 40" / 1016 mm | 40" / 1016 mm |
| Shipping Weight | 200 lb / 91 kg | 300 lb / 136 kg | 350 lb / 159 kg |



RTC

Battery Carts & Carriages

Traveling Battery Transporter

The BHS Traveling Battery Transporter (TBT) has a track mounted design and is available in two models. The TBT is equipped with removable push bars for added convenience and is rated at 2,400 lb (1088 kg) capacity for heavy loads. Notes: Roller height required when ordering. Required track sold separately.

Available Models

TBT-15

TBT-21

Required Accessories

Single Guidance Track - 3" (SGT-C3)

3" (76 mm) C-channel track designed for use with phenolic wheel

Features & Benefits

- Allows for one person changing operations in most applications
- All models meet OSHA safety standards
- Removable push bars for added convenience
- Rated 2,400 lb (1088 kg) capacity for heavy loads
- Spark-proof poly coated rollers make transfers safe and easy
- Track mounted design

Product Specifications

| | TBT-15 | TBT-21 |
|--------------------------|----------------|----------------|
| Compartment Width | 15" / 381 mm | 21" / 533 mm |
| Compartment Depth | 40" / 1016 mm | 40" / 1016 mm |
| Shipping Weight | 150 lb / 68 kg | 175 lb / 79 kg |



TBT shown with SGT-C3 (sold separately)

Battery Carts & Carriages Hardwood Transfer Cart

The BHS Hardwood Transfer Cart (HTC) utilizes plastic lumber decking and is available in two models. The HTC is rated at 3,000 lb (1360 kg) capacity for heavy loads and 6" (152 mm) phenolic casters are standard on all models.

Available Models

HTC-3040

HTC-4040

Features & Benefits

- Plastic interlay lumber deck
- Heavy duty construction for long life and added dependability
- 6" (152 mm) phenolic casters available on all models
- Custom designs available to meet your specifications
- Rated 3,000 lb (1360 kg) capacity for heavy loads

Product Specifications

| | HTC-3040 | HTC-4040 |
|-------------------|----------------|-----------------|
| Overall Width | 34" / 863 mm | 44" / 1117 mm |
| Compartment Width | 30" / 762 mm | 40" / 1016 mm |
| Compartment Depth | 40" / 1016 mm | 40" / 1016 mm |
| Shipping Weight | 200 lb / 91 kg | 230 lb / 104 kg |
| Deck Height | 11" / 279 mm | 11" / 279 mm |



HTC

