



**ELECTRIC 24 VOLT
WALKIE STRADDLE**
3000 / 4000 lbs. (1365 / 1815 kg)



STANDARD SPECIFICATIONS

15/20

Manufacturer's Designation		CS 15	CS 20
Load Capacity / Rated Load @ 24" LC	lbs(kg)	3000 (1365)	4000 (1815)
Height (w/130" Two-Stage)	in(mm)	83 (2108)	83 (2108)
Length to fork face	in(mm)	47.5 (1205)	47.5 (1205)
Right Angle Stack (48"L x 40"W, Add 8" for Clearance)	in(mm)	90 (2286)	90 (2286)
Outside Turning Radius	in(mm)	67.75 (1720)	67.75 (1720)
Travel speed loaded / unloaded	mph(kph)	2.2 (3.5) / 3.5 (5.6)	2.1 (3.4) / 3.5 (5.6)
Power Unit		24 Volt	24 Volt

STANDARD FEATURES

24 volt • Key switch • Emergency power disconnect button • Fused drive and control circuits • High torque drive motor is series wound, fan cooled and has class "H" insulation for maximum protection from heat damage • Heavy duty motor contactors with replaceable tips • Ergonomic design with dual forward/reverse travel controls for thumb operation • Reversing switch at the end of the handle is spring loaded and designed to override the directional control, automatically reversing the truck on contact • Adjustable outriggers



For more information on this model and the full line of CLARK Forklifts, find you local CLARK Dealer at www.clarkmhc.com.