

- Maximize productivity with the highest-in-class reach and lift capacity.
- Move loads confidently using the most responsive hydraulics in the industry.
- Pump up efficiency with the most maneuverable lift on the market.
- Enhance job site safety through unmatched visibility from the cab.
- Stay up and running for years with superior engineering and service.



Get out of the way.



1100 Superior Avenue, Baraga, MI 49908
 800.GO.PETTIBONE
 gopettibone.com



Extendo™ Series

Hands down, it's the hardest-working machine on the job.

With the highest lift capacity in its class, plus unmatched maneuverability, it's the only machine that gets you where you need to go.

MAXIMUM LOAD-HANDLING EFFICIENCY

- Single joystick control for all boom functions
- Rapid-response hydraulic system
- Auxiliary boom tip hydraulics
- Quick disconnect for attachments

POWERFUL MANEUVERABILITY

- Four-wheel drive
- Two-wheel, four-wheel and crab steering
- 12'6" (3.8 m) turn radius
- All models fit under an 8' (2.4 m) doorway

BUILT STRONGEST FOR THE TOUGHEST LOADS AND SITES

- Two wide-stance, heavy-duty lift cylinders
- Automatic fork leveling without slave cylinders
- 24° frame sway (12° left and right of center)
- Rear axle stabilization system¹
- 14.00 x 24 - 16 ply tires²

PEAK PERFORMANCE IN ALL CONDITIONS

- Cummins 110hp, Tier III, turbo diesel engine with full electronic control and protection
- Fully modulated Carraro powershift transmission with four speed forward and reverse with declutch
- Carraro outboard planetary axles with oil-immersed, inboard service and parking brakes

GREATER OPERATING COMFORT AND SAFETY

- Unmatched visibility from the cab
- Adjustable suspension seat with seat belt
- Fully adjustable right-side arm rest
- Full set of gauges for instant machine status

TWO-YEAR, 2,000-HOUR WARRANTY

- The best in its class

¹ Not available on Extendo Series 736.

² 13.00 x 24 - 14 ply tires on Extendo Series 736, 744, 936, 944.



736

Max. lift capacity 7,000 lbs. (3,175 kg)
Max. lift height 36' (11.0 m)
Max. forward reach^A 24' (7.3 m)
Overall height^B 88.5" (2.3 m)
Curb weight^C 21,575 lbs. (9,786 kg)

744

Max. lift capacity 7,000 lbs. (3,175 kg)
Max. lift height 44' 4" (13.5 m)
Max. forward reach^A 30' 3" (9.2 m)
Overall height^B 88.5" (2.3 m)
Curb weight^C 25,075 lbs. (11,374 kg)

936

Max. lift capacity 9,000 lbs. (4,082 kg)
Max. lift height 36' (11.0 m)
Max. forward reach^A 24' (7.3 m)
Overall height^B 91" (2.3 m)
Curb weight^C 25,575 lbs. (11,601 kg)

944

Max. lift capacity 9,000 lbs. (4,082 kg)
Max. lift height 44' 4" (13.5 m)
Max. forward reach^A 30' 3" (9.2 m)
Overall height^B 91" (2.3 m)
Curb weight^C 26,075 lbs. (11,827 kg)

1144

Max. lift capacity 11,000 lbs. (4,990 kg)
Max. lift height 44' 6" (13.6 m)
Max. forward reach^A 30' 3" (9.2 m)
Overall height^B 91.5" (2.3 m)
Curb weight^C 26,575 lbs. (12,054 kg)

1157

Max. lift capacity 11,000 lbs. (4,990 kg)
Max. lift height 57' (17.4 m)
Max. forward reach^A 42' 1" (12.8 m)
Overall height^B 96" (2.4 m)
Curb weight^C 32,575 lbs. (14,776 kg)

^A at 24" load center ^B Boom down ^C Approximate