



CHEETAH

61" & 72" models

The Fastest Cat on Earth.

Specifications

Engine Options:	<ul style="list-style-type: none"> • 27hp Kawasaki FX, air-cooled, V-Twin, vertical shaft • 31hp Kawasaki FX, air-cooled, V-Twin, vertical shaft • 34hp Kohler Command, air-cooled, V-Twin, Electronic Fuel Injection (EFI) • 36hp Briggs Vanguard Big Block, air-cooled, V-Twin, vertical shaft
Fuel Capacity/Design:	15 gallons, dual fuel tanks mounted low on the mower to lower the center-of-gravity and improve hillside stability and traction.
Travel Control:	Twin "Quick-Fit" steering controls with gas dampers for smooth, precise maneuverability. Adjustable to fit various operator sizes. Adjustable damper positions.
Ground Speed:	<ul style="list-style-type: none"> • 16mph forward, 8 mph reverse in high-range • 12mph forward, 5 mph reverse in low-range
Main Frame Construction:	Double tube, steel frame, full-length, fully-welded
Drive Tires:	24 x 12 - 12, 4 ply
Caster Tires:	13 x 6.5 - 6, 4 ply; Flat-Free, semi-pneumatic
Caster Wheel Bearings:	Tapered roller bearings
Front Caster Arm Design:	Bolt-on for easy replacement if necessary
Drive System:	Dual Hydro-Gear ZT-5400, 2-speed, integrated transaxles (2 separate units); 16cc displacement pump; 21cc displacement wheel motor; 9" cooling fan on each unit
Hydraulic Oil Cooling:	Yes - 9" fan on each unit
Hydraulic Oil Filter:	25 micron spin-on filter
Electrical System:	12 Volt battery, 350 cca. Alternator, 20 amp charging. Solenoid shift starter.

WWW.SCAG.COM

(Continued)



Belts:	Kevlar cord. Self-adjusting, spring-loaded, self-tightening
Drive/Load Pulleys:	Split-steel design -- stronger and lighter weight than cast-iron
Instrument Panel :	Ammeter, key switch, throttle, manual choke, BBC switch, digital hour meter
Operator Suspension System:	<ul style="list-style-type: none"> • Isolates the entire operator station from the effects of rough terrain. • <u>Coil-over shock</u> provides effective suspension action right where it's needed, and only where it's needed, for a smooth ride. • <u>High-back seat</u>, fully adjustable, with adjustable, folding arm rests. • "<u>Quick-Fit</u>" <u>steering control levers</u> feature incredible range of adjustment for optimal comfort and control • <u>3-Position adjustable deck lift foot pedal</u> allows for easy deck lift for all operators
PTO - Electric Clutch:	<ul style="list-style-type: none"> • Ogura GT3.5 - 250 ft lb; adjustable air-gap (61" models) • Ogura GT5 - 350 ft lb; adjustable air-gap (72" models)
Cutter Decks:	61" & 72" Velocity Plus side-discharge decks; 61" rear-discharge (RD) deck. Floating, adjustable, anti-scalping design.
Cutter Deck Construction:	Tri-Plate, welded: 10 gauge top, 7 gauge skirts, 7 gauge & 11 gauge reinforcement plates.
Cutter Deck Drive:	Belt-driven -- straight alignment for increased reliability & longevity
Number of Anti-Scalp Wheels:	<ul style="list-style-type: none"> • 61" side-discharge: 7 wheels in 5 positions • 61" rear-discharge: 5 wheels in 3 positions • 72" side-discharge: 7 wheels in 5 positions
Cutter Deck Spindles:	Scag Heavy-Duty Spindles w/cast-iron housing & tapered roller bearings, backed by 3-year limited warranty
Cutter Deck Height Adjustment:	Foot pedal lift (3-position adjustable) with self-locking mechanism at transport position
Cutting Range:	1.25" to 5" in .25" increments
Number of Cutter Blades:	3 Marbain blades
Total Length:	<ul style="list-style-type: none"> • 61" models: 85.5" • 72" models: 91"
Total Width (with discharge chute in mowing position):	<ul style="list-style-type: none"> • 61" models: 73.5" • 61" RD models: 63.5" • 72" models: 83"
Total Width (with discharge chute in transport position):	<ul style="list-style-type: none"> • 61" models: 62.75" • 72" models: 73"
Height (with ROPS):	67"
Height (with ROPS folded):	49.5"
Weight (with ROPS):	<ul style="list-style-type: none"> • 61" models: 1350-1365 lbs. • 72" models: 1385-1400 lbs.
Warranty:	<ul style="list-style-type: none"> • 2 Yr. Commercial Mower Warranty—Parts & labor. • 3 Yr. / 500 Hour Non-Commercial Mower Warranty—Parts & labor. • 3 Yr. Deck Warranty—First & second years parts & labor; third year parts. • 3 Yr. Spindle Warranty—First & second years parts & labor; third year parts. • 2 Yr. Engine Warranty—Minimum two-year warranty covered directly through the individual engine manufacturer.



All specifications subject to change without notice. Actual ground speeds may vary.

WWW.SCAG.COM