

UPENDER (DOWNENDER)



The Southworth hydraulic Upenders are designed for safe and efficient handling of loads up to 6,000 lbs capacity. Large workpieces, flat sheets or rolls can all be repositioned 90° in less than a minute.

30° , 45° and 90°
Upenders/Downenders
are available.

The smooth, positive directing acting hydraulic system allows the operator to stop the tilter anywhere in its travel and hold that position. The standard platen height is 10" -- but heights are available to suit most applications.

The Upender/Downender has an internal hydraulic power unit, plumbed, wired and ready for operation when received. Over center valving maintains the cycle speed for protection of the operator and the load. Platforms are available with "V" decks, conveyor and other accessories to suit most applications.

MODEL NUMBER	CAPACITY CENTERED LOAD LOBS.	UPEND TIME SECONDS	DOWNEND TIME SECONDS	DIMENSIONS INCHES					
				A	B	C	D	E	HP
UP2-90	2,000	14	12	48 to 84	24 to 48	12 to 48	5	25	3.2
UP4-90	4,000	21	17	48 to 84	24 to 48	12 to 48	5	25	3.2
UP-90	6,000	28	23	48 to 84	24 to 48	12 to 48	5	25	3.2



Southworth Products Corp
P.O. Box 380, Portland, ME 04104-1380
Telephone (207) 878-0700 ■ (800) 743-1000
Fax (207) 797-4734
www.SouthworthProducts.com