

# HAULER™ 1200

4X2 GAS  
POWERED  
UTILITY VEHICLE

1,200-lb Load Capacity

9.6 cu-ft Cargo Box Capacity

Limited Slip Differential Option

13.5 HP  
GAS

1200 lb.  
MAX  
LOAD

720 lb.  
MAX  
TOW

9.6 CU FT  
BED  
CARGO



Features and specifications of the vehicles are subject to change without notice.  
Vehicle as photographed may include options not included on base model.

**CUSHMAN™**



**CUSHMAN™**  
LET'S WORK.™

## Built to Handle the Big Jobs

The Cushman Hauler™ 1200 is built to take on the chores that smaller vehicles hide from. With a powerful but fuel-efficient 13.5hp Kawasaki® engine, a 9.6-cubic-foot cargo bed and a total capacity of 1,200 pounds, this machine tears through tough tasks. And an optional limited-slip differential allows the Hauler 1200 to handle wet and loose terrain without tearing up turf. For larger facilities that need more cargo space, the vehicle can be equipped with an optional 14.9-cubic-foot aluminum bed. When your job site needs a big job done fast, you need the Hauler 1200.



## HAULER 1200 GAS UTILITY VEHICLE

DIMENSIONS	
Overall Length	113 in (287 cm)
Overall Width	49.5 in (128 cm)
Overall Height w/o Roof	46.5 in (118 cm)
Overall Height w/Struts & Roof	70.0 in (178 cm)
Wheel Base	77.0 in (196 cm)
Front Wheel Track	37.0 in (94 cm)
Rear Wheel Track	38.0 in (97 cm)
Ground Clearance	4.3 in (11 cm)
Cargo Box Width (inside)	44.0 in (112 cm)
Cargo Box Length (inside)	36.0 in (91 cm)
Cargo Box Depth (inside)	10.5 in (27 cm)
Cargo Box Capacity & Material	9.6 cu ft (0.27 m <sup>3</sup> ) / Roto-molded polyethylene
POWER	
Power Source	4-Cycle, 24.5 ci (401cc) Cylinder
Motor Type/Valve Train	Single Cylinder OHV
Horsepower (kW)	13.5 hp (9.7 kW) Exceeds SAE J1940 Std.
Electrical System	Starter/Generator. Solid State Regulator
Batteries (Qty, Type)	One, 12V Maintenance Free
Drive Train	Continuously Variable Transmission
Oil Filter	Spin-On
Cooling System	Air Cooled
Fuel Capacity	6.0 Gallon (22.7 L) Tank
Gear Selection	Forward - Reverse
Transaxle	Differential with Helical Gears
Rear Axle Ratio	11.42:1(Forward) 15.78:1(Reverse)
PERFORMANCE	
Seating Capacity & Style	2-Person, Bench
Dry Weight	938 lb (425 kg)
Curb Weight (w/ Batteries)	978 lb (443 kg)
Bed Load Capacity	800 lb (363 kg)
Vehicle Load Capacity	1200 lb (545 kg)
Outside Clearance Circle	22.0 ft (6.7 m)
Speed (level ground)	16.5 mph +/- 0.5 mph (25.7 kph +/- 0.8 kph)
Towing Capacity	720 lb (360 kg) max.
STEERING & SUSPENSION	
Steering	Self-compensating Rack & Pinion
Front Suspension	Leaf Springs w/ Hydraulic Shock Absorbers
Rear Suspension	Leaf Springs w/ Hydraulic Shock Absorbers
Service Brake	Rear Wheel Mechanical Self-adjusting Drum
Parking Brake	Self-compensating, Single Point Engagement
Front Tires	Links 18 x 8.5 - 8 (4 Ply Rated)
Rear Tires	Turf Saver 20 x 10.0 - 8
FRAME & COLOR	
Frame	Powder Coated Welded Steel
Front Body & Finish	Injection Molded TPO
Rear Body & Finish	Steel. Base Coat/Clear Coat
Standard Color	Forest Green

### Options & Accessories

- Differential Guard
- Locking Glove Box
- Windshield
- Canopy
- Aluminum Bed
- Taillights
- Brakelights
- Trailer Dump (Steel and Poly)
- Body Color (Ivory, Bright White, Yellow, Orange or Custom Options)
- Turn Signal with Four-Way Flashers
- Strobe Lights
- Work Lights
- Weather Enclosure